CHALMERS FINITE ELEMENT CENTER



PREPRINT 2003–19

Multi-adaptive time integration

Anders Logg



Chalmers Finite Element Center CHALMERS UNIVERSITY OF TECHNOLOGY Göteborg Sweden 2003

CHALMERS FINITE ELEMENT CENTER

Preprint 2003–19

Multi-adaptive time integration

Anders Logg



CHALMERS

Chalmers Finite Element Center Chalmers University of Technology SE–412 96 Göteborg Sweden Göteborg, October 2003

Multi-adaptive time integration Anders Logg

NO 2003–19 ISSN 1404–4382

Chalmers Finite Element Center Chalmers University of Technology SE-412 96 Göteborg Sweden Telephone: +46 (0)31 772 1000 Fax: +46 (0)31 772 3595 www.phi.chalmers.se

Printed in Sweden Chalmers University of Technology Göteborg, Sweden 2003

MULTI-ADAPTIVE TIME INTEGRATION

ANDERS LOGG

ABSTRACT. Time integration of ODEs or time-dependent PDEs with required resolution of the fastest time scales of the system, can be very costly if the system exhibits multiple time scales of different magnitudes. If the different time scales are localised to different components, corresponding to localisation in space for a PDE, efficient time integration thus requires that we use different time steps for different components.

We present an overview of the multi-adaptive Galerkin methods mcG(q) and mdG(q) recently introduced in a series of papers by the author. In these methods, the time step sequence is selected individually and adaptively for each component, based on an a posteriori error estimate of the global error.

The multi-adaptive methods require the solution of large systems of nonlinear algebraic equations which are solved using explicit-type iterative solvers (fixed point iteration). If the system is stiff, these iterations may fail to converge, corresponding to the well-known fact that standard explicit methods are inefficient for stiff systems. To resolve this problem, we present an adaptive strategy for explicit time integration of stiff ODEs, in which the explicit method is adaptively stabilised by a small number of small, stabilising time steps.

1. INTRODUCTION

In earlier work [29, 30], we have introduced the multi-adaptive Galerkin methods mcG(q)and mdG(q) for ODEs of the type

(1.1)
$$\begin{cases} \dot{u}(t) = f(u(t), t), & t \in (0, T], \\ u(0) = u_0, \end{cases}$$

where $u: [0,T] \to \mathbb{R}^N$ is the solution to be computed, $u_0 \in \mathbb{R}^N$ a given initial condition, T > 0 a given final time, and $f: \mathbb{R}^N \times (0,T] \to \mathbb{R}^N$ a given function that is Lipschitzcontinuous in u and bounded. We use the term *multi-adaptivity* to describe methods with individual time-stepping for the different components $u_i(t)$ of the solution vector $u(t) = (u_i(t))$, including (i) time step length, (ii) order, and (iii) quadrature, all chosen adaptively in a computational feed-back process.

Surprisingly, individual time-stepping for ODEs has received little attention in the large literature on numerical methods for ODEs, see e.g. [4, 24, 25, 2, 34]. For specific applications, such as the *n*-body problem, methods with individual time-stepping have been used, see e.g. [31, 1, 5], but a general methodology has been lacking. For time-dependent PDEs,

Date: October 30, 2003.

Key words and phrases. Multi-adaptivity, error control, adaptivity, explicit, stiffness.

Anders Logg, Department of Computational Mathematics, Chalmers University of Technology, S–412 96 Göteborg, Sweden, *email*: logg@math.chalmers.se.

in particular for conservation laws of the type $\dot{u} + f(u)_x = 0$, attempts have been made to construct methods with individual (locally varying in space) time steps. Flaherty et al. [22] have constructed a method based on the discontinuous Galerkin method combined with local explicit Euler time-stepping. A similar approach is taken in [6] where a method based on the original work by Osher and Sanders [32] is presented for conservation laws in one and two space dimensions. Typically the time steps used are based on local CFL conditions rather than error estimates for the global error and the methods are low order in time (meaning ≤ 2). We believe that our work on multi-adaptive Galerkin methods (including error estimation and arbitrary order methods) presents a general methodology to individual time-stepping, which will result in efficient integrators both for ODEs and time-dependent PDEs.

The multi-adaptive methods are developed within the general framework of adaptive Galerkin methods based on piecewise polynomial approximation (finite element methods) for differential equations, including the continuous and discontinuous Galerkin methods cG(q) and dG(q) which we extend to their multi-adaptive analogues mcG(q) and mdG(q). Earlier work on adaptive error control for the cG(q) and dG(q) methods include [7, 17, 27, 19, 18, 21]. See also [10, 11, 9, 12, 13, 14], and [8] or [20] in particular for an overview of adaptive error control based on duality techniques. The approach to error analysis and adaptivity presented in these references naturally carries over to the multi-adaptive methods.

1.1. The stiffness problem. The classical wisdom developed in the 1950s regarding stiff ODEs is that efficient integration requires implicit (A-stable) methods, at least outside transients where the time steps may be chosen large from accuracy point of view. Using an explicit method (with a bounded stability region) the time steps have to be small at all times for stability reasons, in particular outside transients, and the advantage of a low cost per time step for the explicit method is counter-balanced by the necessity of taking a large number of small time steps. As a result, the overall efficiency of an explicit method for a stiff ODE is small.

We encounter the same problem when we try to use explicit fixed point iteration to solve the discrete equations given by the multi-adaptive Galerkin methods mcG(q) and mdG(q). However, it turns out that if a sequence of large (unstable) time steps are accompanied by a suitable (small) number of small time steps, a stiff system can be stabilised to allow integration with an effective time step much larger than the largest stable time step given by classical stability analysis. This idea of stabilising a stiff system using the inherent damping property of the stiff system itself was first developed in an automatic and adaptive setting in [16], and will be further explored in the full multi-adaptive setting. A similar approach is taken in recent independent work by Gear and Kevrekidis [3]. The relation to Runge-Kutta methods based on Chebyshev polynomials discussed by Verwer in [26] should also be noted.

1.2. Notation. The following notation is used in the discussion of the multi-adaptive Galerkin methods below: Each component $U_i(t)$, i = 1, ..., N, of the approximate m(c/d)G(q)

solution U(t) of (1.1) is a piecewise polynomial on a partition of (0, T] into M_i subintervals. Subinterval j for component i is denoted by $I_{ij} = (t_{i,j-1}, t_{ij}]$, and the length of the subinterval is given by the local time step $k_{ij} = t_{ij} - t_{i,j-1}$. This is illustrated in Figure 1. On each subinterval I_{ij} , $U_i|_{I_{ij}}$ is a polynomial of degree q_{ij} and we refer to $(I_{ij}, U_i|_{I_{ij}})$ as an element.

Furthermore, we shall assume that the interval (0, T] is partitioned into blocks between certain synchronised time levels $0 = T_0 < T_1 < \ldots < T_M = T$. We refer to the set of intervals \mathcal{T}_n between two synchronised time levels T_{n-1} and T_n as a time slab: $\mathcal{T}_n = \{I_{ij}:$ $T_{n-1} \leq t_{i,j-1} < t_{ij} \leq T_n\}$, and we denote the length of a time slab by $K_n = T_n - T_{n-1}$. The partition consisting of the entire collection of intervals is denoted by $\mathcal{T} = \bigcup \mathcal{T}_n$.



FIGURE 1. Individual partitions of the interval (0, T] for different components. Elements between common synchronised time levels are organised in time slabs. In this example, we have N = 6 and M = 4.

1.3. Outline. The outline of the paper is as follows: In Section 2, we formulate the multiadaptive Galerkin methods mcG(q) and mdG(q). In Section 3, we discuss error control and adaptivity. In particular, we show how to choose the individual time steps based on an a posteriori error estimate for the global error. In Section 4, we give a quick overview of an iterative method (based on fixed point iteration) for the system of nonlinear discrete equations that needs to be solved on each time slab, and in Section 5 we describe a technique that can be used to stabilise the explicit fixed point iterations for stiff problems. Finally, in Section 6, we present a number of numerical examples chosen to illustrate both the potential of multi-adaptivity and the use of explicit fixed point iteration (or explicit timestepping) for stiff problems.

2. Multi-Adaptive Galerkin

2.1. Multi-adaptive continuous Galerkin, mcG(q). To give the definition of the mcG(q) method, we define the *trial space* V and the *test space* W as

(2.1)
$$V = \{ v \in [\mathcal{C}([0,T])]^N : v_i|_{I_{ij}} \in \mathcal{P}^{q_{ij}}(I_{ij}), \ j = 1, \dots, M_i, \ i = 1, \dots, N \}, \\ W = \{ v : v_i|_{I_{ij}} \in \mathcal{P}^{q_{ij}-1}(I_{ij}), \ j = 1, \dots, M_i, \ i = 1, \dots, N \},$$

where $\mathcal{P}^{q}(I)$ denotes the linear space of polynomials of degree $q \geq 0$ on the interval I. In other words, V is the space of continuous piecewise polynomials of degree $q = q_i(t) = q_{ij}, t \in I_{ij}$ on the partition \mathcal{T} , and W is the space of (in general discontinuous) piecewise polynomials of degree q - 1 on the same partition.

We define the mcG(q) method for (1.1) as follows: Find $U \in V$ with $U(0) = u_0$, such that

(2.2)
$$\int_0^T (\dot{U}, v) \, dt = \int_0^T (f(U, \cdot), v) \, dt \quad \forall v \in W,$$

where (\cdot, \cdot) denotes the standard inner product in \mathbb{R}^N . If now for each local interval I_{ij} we take $v_n = 0$ when $n \neq i$ and $v_i(t) = 0$ when $t \notin I_{ij}$, we can rewrite the global problem (2.2) as a number of successive local problems for each component: For $i = 1, \ldots, N$, $j = 1, \ldots, M_i$, find $U_i|_{I_{ij}} \in \mathcal{P}^{q_{ij}}(I_{ij})$ with $U_i(t_{i,j-1})$ given from the previous time interval, such that

(2.3)
$$\int_{I_{ij}} \dot{U}_i v \ dt = \int_{I_{ij}} f_i(U, \cdot) v \ dt \quad \forall v \in \mathcal{P}^{q_{ij}-1}(I_{ij}).$$

We define the residual R of the approximate solution U to be $R(U,t) = \dot{U}(t) - f(U(t),t)$. In terms of the residual, we can rewrite (2.3) as $\int_{I_{ij}} R_i(U,\cdot)v \, dt = 0$ for all $v \in \mathcal{P}^{q_{ij}-1}(I_{ij})$, i.e., the residual is orthogonal to the test space on every local interval. We refer to this as the *Galerkin orthogonality* of the mcG(q) method.

2.2. Multi-adaptive discontinuous Galerkin, mdG(q). For the mdG(q) method, we define the trial and test spaces by

(2.4)
$$V = W = \{ v : v_i |_{I_{ij}} \in \mathcal{P}^{q_{ij}}(I_{ij}), j = 1, \dots, M_i, i = 1, \dots, N \},$$

i.e., both trial and test functions are (in general discontinuous) piecewise polynomials of degree $q = q_i(t) = q_{ij}$, $t \in I_{ij}$ on the partition \mathcal{T} .

We define the mdG(q) method for (1.1) as follows, similar to the definition of the continuous method: Find $U \in V$ with $U(0^-) = u_0$, such that

(2.5)
$$\sum_{i=1}^{N} \sum_{j=1}^{M_{i}} \left[[U_{i}]_{i,j-1} v(t_{i,j-1}^{+}) + \int_{I_{ij}} \dot{U}_{i} v_{i} dt \right] = \int_{0}^{T} (f(U, \cdot), v) dt \quad \forall v \in W.$$

where [·] denotes the jump, i.e., $[v]_{ij} = v(t_{ij}^+) - v(t_{ij}^-)$.

The mdG(q) method in local form, corresponding to (2.3), reads: For i = 1, ..., N, $j = 1, ..., M_i$, find $U_i|_{I_{ij}} \in \mathcal{P}^{q_{ij}}(I_{ij})$, such that

(2.6)
$$[U_i]_{i,j-1}v(t_{i,j-1}) + \int_{I_{ij}} \dot{U}_i v \ dt = \int_{I_{ij}} f_i(U, \cdot)v \ dt \quad \forall v \in \mathcal{P}^{q_{ij}}(I_{ij}),$$

where the initial condition is specified for i = 1, ..., N, by $U_i(0^-) = u_i(0)$. In the same way as for the continuous method, we define the residual R of the approximate solution U to be $R(U,t) = \dot{U}(t) - f(U(t),t)$, defined on the inner of every local interval I_{ij} , and rewrite (2.6) in the form $[U_i]_{i,j-1}v(t_{i,j-1}) + \int_{I_{ij}} R_i(U,\cdot)v \ dt = 0$ for all $v \in \mathcal{P}^{q_{ij}}(I_{ij})$. We refer to this as the Galerkin orthogonality of the mdG(q) method.

3. Error Control and Adaptivity

Our goal is to compute an approximation U(T) of the exact solution u(T) of (1.1) at final time T within a given tolerance TOL > 0, using a minimal amount of computational work. This goal includes an aspect of *reliability* (the error should be less than the tolerance) and an aspect of *efficiency* (minimal computational work). To measure the error we choose a norm, such as the Euclidean norm $\|\cdot\|$ on \mathbb{R}^N , or more generally some other quantity of interest.

We discuss below both a priori and a posteriori error estimates for the multi-adaptive Galerkin methods, and the application of the a posteriori error estimates in multi-adaptive time-stepping.

3.1. A priori error estimates. Standard (duality-based) a priori error estimates show that the order for the ordinary Galerkin methods cG(q) and dG(q) is 2q and 2q + 1, respectively. A generalisation of these estimates to the multi-adaptive methods gives the same result. The multi-adaptive continuous Galerkin method mcG(q) is thus of order 2q, and the multi-adaptive discontinuous Galerkin method mdG(q) is of order 2q + 1.

3.2. A posteriori error estimates. A posteriori error analysis in the general framework of [8] relies on the concept of the *dual problem*. The dual problem of the initial value problem (1.1) is the linearised backward problem given by

(3.1)
$$\begin{cases} -\dot{\phi} = J^*(u, U, \cdot)\phi & \text{on } [0, T), \\ \phi(T) = e(T)/\|e(T)\|, \end{cases}$$

where the Jacobian J is given by $J(u, U, \cdot) = \int_0^1 \frac{\partial f}{\partial u} (su + (1 - s)U, \cdot) ds$ and * denotes the transpose. We use the dual problem to represent the error in terms of the dual solution ϕ and the residual R. For the mcG(q) method the representation formula is given by

(3.2)
$$||e(T)|| = \int_0^T (R,\phi) dt,$$

and for the mdG(q) method, we obtain

(3.3)
$$\|e(T)\| = \sum_{i=1}^{N} \sum_{j=1}^{M_i} [U_i]_{i,j-1} \phi_i(t_{i,j-1}) + \int_{I_{ij}} R_i(U, \cdot) \phi_i dt.$$

Using the Galerkin orthogonalities together with special interpolation estimates (see [29]), we obtain a posteriori error estimates of the form

(3.4)
$$||e(T)|| \leq \sum_{i=1}^{N} S_{i}^{[q_{i}]} \max_{[0,T]} \{Ck_{i}^{q_{i}}r_{i}\},$$

for the mcG(q) method, and

(3.5)
$$||e(T)|| \le \sum_{i=1}^{N} S_i^{[q_i+1]} \max_{[0,T]} \left\{ Ck_i^{q_i+1}r_i \right\},$$

for the mdG(q) method, where C is an interpolation constant, r_i is a local measure of the residual, and the individual stability factors S_i are given by $S_i^{[q_i]} = \int_0^T |\phi_i^{(q_i)}| dt$. Typically, the stability factors are of moderate size for a stiff problem (and of unit size for a parabolic problem), which means that accurate computation is possible over long time intervals. Note that the Lipschitz constant, which is large for a stiff problem, is not present in these estimates.

The analysis can be extended to include also *computational errors*, arising from solving the discrete equations using an iterative method, and *quadrature errors*, arising from evaluating the integrals in (2.3) and (2.6) using quadrature.

3.3. Adaptivity. To achieve the goals stated at the beginning of this section, the adaptive algorithm chooses individual time steps for the different components based on the a posteriori error estimates. Using for example a standard *PID* regulator from control theory, we choose the individual time steps for each component to satisfy

$$(3.6) S_i C k_{ij}^{p_{ij}} r_{ij} = \mathrm{TOL}/N$$

or, taking the logarithm with $C_i = \log(\text{TOL}/(NS_iC))$,

$$(3.7) p_{ij}\log k_{ij} + \log r_{ij} = C_i$$

with maximal time steps $\{k_{ij}\}$, following work by Söderlind and coworkers [23, 35]. Here, $p_{ij} = q_{ij}$ for the mcG(q) method and $p_{ij} = q_{ij} + 1$ for the mdG(q) method.

To solve the dual problem (3.1), which is needed to compute the stability factors, it would seem that we need to know the error e(T), since this is used as an initial value for the dual problem. However, we know from experience that the stability factors are quite insensitive to the choice of initial data for the dual problem. (A motivation of this for parabolic problems is given in [15].) Thus in practice, a random (and normalised) value is chosen as initial data for the dual problem. Another approach is to take the initial value for the dual problem to be $\phi(T) = (0, \ldots, 0, 1, 0, \ldots, 0)$, i.e., a vector of zeros except for a single component which is of size one. This gives an estimate for a chosen component of the error. By other choices of data for the dual problem, other functionals of the error can be controlled. In either case, the stability factors are computed using quadrature from the computed dual solution.

The adaptive algorithm can be expressed as follows: Given a tolerance TOL > 0, make a preliminary estimate for the stability factors and then

- (i) Solve the primal problem with time steps based on (3.6);
- (ii) Solve the dual problem and compute the stability factors;
- (iii) Compute an error bound E based on (3.2) or (3.3);
- (iv) If $E \leq \text{TOL}$ then stop; if not go back to (i).

Note that we use the error representations (3.2) and (3.3) to obtain sharp error estimates. On the other hand, the error estimates (3.4) and (3.5) are used to determine the adaptive time step sequences.

To limit the computational work, it is desirable that only a few iterations in the adaptive algorithm are needed. In the simplest case, the error estimate will stay below the given tolerance on the first attempt. Otherwise, the algorithm will try to get below the tolerance the second time. It is also possible to limit the number of times the dual problem is solved. It should also be noted that to obtain an error estimate at a time $t = \bar{t}$, different from the final time T, the dual problem has to be solved backwards also from time \bar{t} . This may be necessary in some cases if the stability factors do not grow monotonically as functions of the final time T, but for many problems the stability factors grow with T, indicating accumulation of errors.

Our experience is that automatic computation based on this adaptive strategy is both reliable (the error estimates are quite close to the actual error) and efficient (the additional cost for solving the dual problem is quite small). See [28] for a discussion on this topic.

4. Iterative Methods for the Nonlinear System

The nonlinear discrete algebraic equations given by the mcG(q) and mdG(q) methods presented in Section 2 (including numerical quadrature) to be solved on every local interval I_{ij} take the form

(4.1)
$$\xi_{ijm} = \xi_{ij0} + k_{ij} \sum_{n=0}^{q_{ij}} w_{mn}^{[q_{ij}]} f_i(U(\tau_{ij}^{-1}(s_n^{[q_{ij}]})), \tau_{ij}^{-1}(s_n^{[q_{ij}]})),$$

for $m = 0, \ldots, q_{ij}$, where $\{\xi_{ijm}\}_{m=0}^{q_{ij}}$ are the degrees of freedom to be determined for component $U_i(t)$ on the interval I_{ij} , $\{w_{mn}^{[q_{ij}]}\}_{m=0,n=0}^{q_{ij}}$ are weights, τ_{ij} maps I_{ij} to (0,1]: $\tau_{ij}(t) = (t - t_{i,j-1})/(t_{ij} - t_{i,j-1})$, and $\{s_n^{[q_{ij}]}\}_{n=0}^{q_{ij}}$ are quadrature points defined on [0,1].

The strategy we use to solve the discrete equations (4.1) is by direct fixed point iteration, possibly in combination with a simplified Newton's method. To evolve the system, we need to collect the degrees of freedom for different components between two time levels and solve the discrete equations for these degrees of freedom. We refer to such a collection of elements between two time levels as a time slab (see Figure 1). New time slabs are formed as we evolve the system starting at time t = 0, in the same way as new time intervals are formed

in a standard solver which uses the same time steps for all components. On each time slab, we thus compute the degrees of freedom $\{\xi_{ijm}\}_{m=0}^{q_{ij}}$ for each element within the time slab using (4.1), and repeat the iterations until the computational error is below a given tolerance for the computational error. The iterations are carried out in order, starting at the element closest to time t = 0 and continuing until we reach the last element within the time slab. This is illustrated in Figure 2.



FIGURE 2. Multi-adaptive time-stepping within a time slab for a system with two components.

The motivation for using direct fixed point iteration, rather than using a full Newton's method, is that we want to avoid forming the Jacobian (which may be very large, since the nonlinear system to be solved is for the entire time slab) and also avoid solving the linearised system. Instead, using the strategy for adaptive damping of the fixed point iterations as described in the next section, the linear algebra is built into the adaptive solver. Since often only a small number of fixed point iterations are needed, typically only two or three iterations, we believe this to be an efficient approach.

5. Stiff Problems

As discussed in the previous section, the nonlinear discrete equations given by the (implicit) multi-adaptive Galerkin methods are solved using fixed point iteration on each time slab. For stiff problems these iterations may fail to converge. We now discuss a simple way to stabilise a stiff system, in order to make the explicit fixed point iterations convergent.

For simplicity, we assume that the time step sequence, k_1, k_2, \ldots, k_M , is the same for all components.

5.1. The test equation. To demonstrate the main idea, we consider the stabilisation of the explicit Euler method applied to the simple *test equation*:

(5.1)
$$\begin{cases} \dot{u}(t) + \lambda u(t) = 0 & \text{for } t > 0, \\ u(0) = u_0, \end{cases}$$

where $\lambda > 0$ and u_0 is a given initial condition. The solution is given by $u(t) = \exp(-\lambda t)u_0$. The explicit Euler method for the test equation reads

$$U^{n} = U^{n-1} - k_n \lambda U^{n-1} = (1 - k_n \lambda) U^{n-1}.$$

This method is conditionally stable, with stability guaranteed if $k_n \lambda \leq 2$. If λ is large, this is too restrictive outside transients.

Now, let K be a large time step satisfying $K\lambda > 2$ and let k a small time step chosen so that $k\lambda < 2$. Consider the method

(5.2)
$$U^{n} = (1 - k\lambda)^{m} (1 - K\lambda) U^{n-1},$$

corresponding to one explicit Euler step with large time step K and m explicit Euler steps with small time steps k, where m is a positive integer to be determined. Altogether this corresponds to a time step of size $k_n = K + mk$. For the overall method to be stable, we require that $|1 - k\lambda|^m (K\lambda - 1) \leq 1$, that is

(5.3)
$$m \ge \frac{\log(K\lambda - 1)}{-\log|1 - k\lambda|} \approx \frac{\log(K\lambda)}{c},$$

if $K\lambda \gg 1$ and $c = k\lambda$ is of moderate size, say c = 1/2.

We conclude that m will be quite small and hence the small time steps will be used only in a small fraction of the total time interval, giving a large effective time step. To see this, define the *cost* as $\alpha = \frac{1+m}{K+km} \in (1/K, 1/k)$, i.e., the number of time steps per unit interval. Classical stability analysis gives $\alpha = 1/k = \lambda/2$ with a maximum time step $k = 2/\lambda$. Using (5.3) we instead find

(5.4)
$$\alpha \approx \frac{1 + \log(K\lambda)/c}{K + \log(K\lambda)/\lambda} \approx \frac{\lambda}{c} \log(K\lambda)/(K\lambda) \ll \lambda/c,$$

for $K\lambda \gg 1$. The cost is thus decreased by the cost reduction factor

$$\frac{2\log(K\lambda)}{cK\lambda} \sim \frac{\log(K\lambda)}{K\lambda}$$

which can be quite significant for large values of $K\lambda$.

5.2. The general non-linear problem. For the general nonlinear problem (1.1), the gain is determined by the distribution of the eigenvalues of the Jacobian, see [16]. The method of stabilising the system using a couple of small stabilising time steps is best suited for systems with a clear separation of the eigenvalues into small and large eigenvalues, but even for the semi-discretised heat equation (for which we have a whole range of eigenvalues) the gain can be substantial, as we shall see below.

5.3. An adaptive algorithm. In [16] we present an adaptive algorithm in which both the size of the small stabilising time steps and the number of such small time steps are automatically determined. Using adaptive stabilisation, the damping is targeted precisely at the current unstable eigenmode, which as a consequence allows efficient integration also of problems with no clear separation of its eigenvalues.

6. Numerical Examples

The numerical examples presented in this section are divided into two categories: examples illustrating the concept of multi-adaptivity and examples illustrating explicit timestepping (or explicit fixed point iteration) for stiff problems.

6.1. Multi-adaptivity. The two examples presented below are taken from [30], in which further examples are presented and discussed in more detail.

6.1.1. A mechanical multi-scale system. To demonstrate the potential of the multi-adaptive methods, we consider a dynamical system in which a small part of the system oscillates rapidly. The problem is to compute accurately the positions (and velocities) of the N point-masses attached together with springs of equal stiffness as in Figure 3.



FIGURE 3. A mechanical system consisting of N = 5 masses attached together with springs.

We choose a small time step for the smallest mass and large time steps for the larger masses, and measure the work for the mcG(1) method as we increase the number of larger masses. The work is then compared to the work required for the standard cG(1) method using the same (small) time step for all masses. As is evident in Figure 4, the work (in terms of function evaluations) increases linearly for the standard method, whereas for the multi-adaptive method it remains practically constant.

6.1.2. Reaction-diffusion. Next consider the following system of PDEs:

(6.1)
$$\begin{cases} \dot{u}_1 - \epsilon u_1'' = -u_1 u_2^2 \\ \dot{u}_2 - \epsilon u_2'' = u_1 u_2^2, \end{cases}$$

on $(0, 1) \times (0, T]$ with $\epsilon = 0.001$, T = 100 and homogeneous Neumann boundary conditions at x = 0 and x = 1, which models isothermal auto-catalytic reactions (see [33]): $A_1+2A_2 \rightarrow A_2 + 2A_2$. As initial conditions, we take $u_1(x, 0) = 0$ for $0 < x < x_0$, $u_1(x, 0) = 1$ for $x_0 \leq x < 1$, and $u_2(x, 0) = 1 - u_1(x, 0)$ with $x_0 = 0.2$. An initial reaction where substance A_1 is consumed and substance A_2 is formed will then take place at $x = x_0$, resulting in a decrease in the concentration u_1 and an increase in the concentration u_2 . The reaction then propagates to the right until all of substance A_1 is consumed and we have $u_1 = 0$ and $u_2 = 1$ in the entire domain.

Computing the solution using the mcG(2) method, we find that the time steps are automatically chosen to be small only in the vicinity of the reaction front, see Figure 5, and during the computation the region of small time steps will propagate to the right at the same speed as the reaction front.



FIGURE 4. Error, cpu time, total number of steps, and number of function evaluations as function of the number of masses, for the multi-adaptive cG(1) method (dashed) and the standard cG(1) method (solid).



FIGURE 5. The concentrations of the two species, U_1 and U_2 , at time t = 50 as function of space (above), and the corresponding time steps (below).

6.2. Explicit time-stepping for stiff problems. To illustrate the technique of stabilisation for stiff problems, we present below some examples taken from [16]. In these examples, the cost α is compared to the cost α_0 of a standard implementation of the cG(1) method in which we are forced to take a small time step all the time. (These small time steps are marked by dashed lines in the figures.) Comparison has not been made with an implicit

method, since it would be difficult to make such a comparison fair; one could always argue about the choice of linear solver and preconditioner. However, judging by the modest restriction of the average time step size and the low cost of the explicit method, we believe our approach to be competitive also with implicit methods, although this remains to be seen.

6.2.1. The test equation. The first problem we try is the test equation:

(6.2)
$$\begin{cases} \dot{u}(t) + \lambda u(t) = 0 \text{ for } t > 0, \\ u(0) = u_0, \end{cases}$$

on [0, 10], where we choose $u_0 = 1$ and $\lambda = 1000$. As is shown in Figure 6, the time step is repeatedly decreased to stabilise the stiff system, but overall the effective time step is large and the cost reduction factor is $\alpha/\alpha_0 \approx 1/310$.



FIGURE 6. Solution and time step sequence for eq. (6.2), $\alpha/\alpha_0 \approx 1/310$.

6.2.2. The test system. For the test system,

(6.3)
$$\begin{cases} \dot{u}(t) + Au(t) = 0 \text{ for } t > 0, \\ u(0) = u_0, \end{cases}$$

on [0, 10], we take A = diag(100, 1000) and $u_0 = (1, 1)$. As seen in Figure 7, most of the stabilising steps are chosen to damp out the eigenmode corresponding to the largest eigenvalue, $\lambda_2 = 1000$, but some of the damping steps are targeted at the second eigenvalue, $\lambda_1 = 100$. The selective damping is handled automatically by the adaptive algorithm and the cost reduction factor is again significant: $\alpha/\alpha_0 \approx 1/104$.



FIGURE 7. Solution and time step sequence for eq. (6.3), $\alpha/\alpha_0 \approx 1/104$.

6.2.3. *The HIRES problem.* The so-called HIRES problem ("High Irradiance RESponse") originates from plant physiology and is taken from the test set of ODE problems compiled by Lioen and de Swart [36]. The problem consists of the following eight equations:

$$(6.4) \qquad \begin{cases} \dot{u}_1 = -1.71u_1 + 0.43u_2 + 8.32u_3 + 0.0007, \\ \dot{u}_2 = 1.71u_1 - 8.75u_2, \\ \dot{u}_3 = -10.03u_3 + 0.43u_4 + 0.035u_5, \\ \dot{u}_4 = 8.32u_2 + 1.71u_3 - 1.12u_4, \\ \dot{u}_5 = -1.745u_5 + 0.43u_6 + 0.43u_7, \\ \dot{u}_6 = -280.0u_6u_8 + 0.69u_4 + 1.71u_5 - 0.43u_6 + 0.69u_7, \\ \dot{u}_7 = 280.0u_6u_8 - 1.81u_7, \\ \dot{u}_8 = -280.0u_6u_8 + 1.81u_7, \end{cases}$$

on [0, 321.8122] (as specified in [36]). The initial condition is given by $u_0 = (1.0, 0, 0, 0, 0, 0, 0, 0.0057)$. The cost reduction factor is now $\alpha/\alpha_0 \approx 1/33$, see Figure 8.

6.3. The heat equation. Finally, we consider the heat equation in one dimension:

(6.5)
$$\begin{cases} \dot{u}(x,t) - u''(x,t) = f(x,t), & x \in (0,1), \ t > 0, \\ u(0) = u(1) = 0, \\ u(\cdot,t) = 0, \end{cases}$$

where we choose f(x,t) = f(x) as an approximation of the Dirac delta function at x = 0.5. Discretising in space, we obtain the ODE

(6.6)
$$\begin{cases} \dot{u}(t) + Au(t) = f, \quad t > 0, \\ u(0) = 0, \end{cases}$$



FIGURE 8. Solution and time step sequence for eq. (6.4), $\alpha/\alpha_0 \approx 1/33$.

where A is the stiffness matrix. With a spatial resolution of h = 0.01, the eigenvalues of A are distributed in the interval $[0, 4 \cdot 10^4]$ (see Figure 9). The selective damping produced by the adaptive algorithm performs well and the cost reduction factor is $\alpha/\alpha_0 \approx 1/17$.



FIGURE 9. Solution and time step sequence for eq. (6.6), $\alpha/\alpha_0 \approx 1/17$.

References

- [1] S. ALEXANDER AND C. AGNOR, N-body simulations of late stage planetary formation with a simple fragmentation model, ICARUS, 132 (1998), pp. 113–124.
- [2] J. BUTCHER, The Numerical Analysis of Ordinary Differential Equations Runge-Kutta and General Linear Methods, Wiley, 1987.
- [3] C.W. GEAR AND I.G. KEVREKIDIS, Projective methods for stiff differential equations: problems with gaps in their eigenvalue spectrum, submitted to SIAM J. Sci. Comp., (2001).
- [4] G. DAHLQUIST, Stability and Error Bounds in the Numerical Integration of Ordinary Differential Equations, PhD thesis, Trans. of the Royal Inst. of Techn., Stockholm, Sweden, Number 130, Uppsala, 1958.
- [5] R. DAVE, J. DUBINSKI, AND L. HERNQUIST, Parallel TreeSPH, New Astronomy, 2 (1997), pp. 277–297.
- [6] C. DAWSON AND R. KIRBY, High resolution schemes for conservation laws with locally varying time steps, SIAM J. Sci. Comput., 22, No. 6 (2001), pp. 2256–2281.
- [7] M. DELFOUR, W. HAGER, AND F. TROCHU, Discontinuous Galerkin methods for ordinary differential equations, Math. Comp., 36 (1981), pp. 455–473.
- [8] K. ERIKSSON, D. ESTEP, P. HANSBO, AND C. JOHNSON, Introduction to adaptive methods for differential equations, in Acta Numerica 1995, Cambridge University Press, 1995, pp. 105–158.
- [9] K. ERIKSSON AND C. JOHNSON, Adaptive finite element methods for parabolic problems III: Time steps variable in space, in preparation / personal communication.
- [10] —, Adaptive finite element methods for parabolic problems I: A linear model problem, SIAM J. Numer. Anal., 28, No. 1 (1991), pp. 43–77.
- [11] —, Adaptive finite element methods for parabolic problems II: Optimal order error estimates in $L_{\infty}L_2$ and $L_{\infty}L_{\infty}$, SIAM J. Numer. Anal., 32 (1995), pp. 706–740.
- [12] —, Adaptive finite element methods for parabolic problems IV: Nonlinear problems, SIAM J. Numer. Anal., 32 (1995), pp. 1729–1749.
- [13] ____, Adaptive finite element methods for parabolic problems V: Long-time integration, SIAM J. Numer. Anal., 32 (1995), pp. 1750–1763.
- [14] K. ERIKSSON, C. JOHNSON, AND S. LARSSON, Adaptive finite element methods for parabolic problems VI: Analytic semigroups, SIAM J. Numer. Anal., 35 (1998), pp. 1315–1325.
- [15] K. ERIKSSON, C. JOHNSON, AND A. LOGG, Adaptive computational methods for parabolic problems. Submitted to Encyclopedia of Computational Mechanics, March 2003.
- [16] —, *Explicit time-stepping for stiff ODEs*, SIAM J. Sci. Comput., To appear (2003).
- [17] K. ERIKSSON, C. JOHNSON, AND V. THOME, Time discretization of parabolic problems by the discontinuous Galerkin method, RAIRO MAN, 19 (1985), pp. 611–643.
- [18] D. ESTEP, A posteriori error bounds and global error control for approximations of ordinary differential equations, SIAM J. Numer. Anal., 32 (1995), pp. 1–48.
- [19] D. ESTEP AND D. FRENCH, Global error control for the continuous Galerkin finite element method for ordinary differential equations, M²AN, 28 (1994), pp. 815–852.
- [20] D. ESTEP, M.G. LARSON, AND R. WILLIAMS, Estimating the error of numerical solutions of systems of reaction-diffusion equations, Mem. Amer. Math. Soc., 146 (2000), pp. 1–109.
- [21] D. ESTEP AND R. WILLIAMS, Accurate parallel integration of large sparse systems of differential equations, Math. Models. Meth. Appl. Sci., 6 (1996), pp. 535–568.
- [22] J. FLAHERTY, R. LOY, M. SHEPHARD, B. SZYMANSKI, J. TERESCO, AND L. ZIANTZ, Adaptive local refinement with octree load balancing for the parallel solution of three-dimensional conservation laws, Journal of Parallel and Distributed Computing, 47 (1997), pp. 139–152.
- [23] K. GUSTAFSSON, M. LUNDH, AND G. SÖDERLIND, A PI stepsize control for the numerical solution of ordinary differential equations, BIT, 28 (1988), pp. 270–287.

- [24] E. HAIRER AND G. WANNER, Solving Ordinary Differential Equations I Nonstiff Problems, Springer Series in Computational Mathematics, vol 8, 1991.
- [25] —, Solving Ordinary Differential Equations II Stiff and Differential-Algebraic Problems, Springer Series in Computational Mathematics, vol 14, 1991.
- [26] J.G. VERWER, Explicit Runge-Kutta methods for parabolic partial differential equations, Appl. Numer. Math., 22 (1996), pp. 359–379.
- [27] C. JOHNSON, Error estimates and adaptive time-step control for a class of one-step methods for stiff ordinary differential equations, SIAM J. Numer. Anal., 25, No. 4 (1988), pp. 908–926.
- [28] A. LOGG, Multi-adaptive Galerkin methods for ODEs II: Applications, Chalmers Finite Element Center Preprint 2001–10, (2001).
- [29] —, Multi-adaptive Galerkin methods for ODEs I, SIAM J. Sci. Comput., 24 (2003), pp. 1879–1902.
- [30] —, Multi-adaptive Galerkin methods for ODEs II: Implementation and applications, SIAM J. Sci. Comput., (2003). To appear.
- [31] J. MAKINO AND S. AARSETH, On a Hermite integrator with Ahmad-Cohen scheme for gravitational many-body problems, Publ. Astron. Soc. Japan, 44 (1992), pp. 141–151.
- [32] S. OSHER AND R. SANDERS, Numerical approximations to nonlinear conservation laws with locally varying time and space grids, Math. Comp., 41 (1983), pp. 321–336.
- [33] R. SANDBOGE, Adaptive Finite Element Methods for Reactive Flow Problems, PhD thesis, Department of mathematics, Chalmers University of Technology, Göteborg, 1996.
- [34] L. SHAMPINE, Numerical Solution of Ordinary Differential Equations, Chapman & Hall, 1994.
- [35] G. SÖDERLIND, The automatic control of numerical integration, CWI Quarterly, 11 (1998), pp. 55–74.
- [36] W.M. LIOEN AND J.J.B. DE SWART, Test set for initial value problem solvers, CWI Report MAS-R9832, ISSN 1386–3703, Amsterdam, (1998).

Chalmers Finite Element Center Preprints

2001–01	A simple nonconforming bilinear element for the elasticity problem Peter Hansbo and Mats G. Larson
2001 - 02	The \mathcal{LL}^* finite element method and multigrid for the magnetostatic problem Rickard Bergström, Mats G. Larson, and Klas Samuelsson
2001–03	The Fokker-Planck operator as an asymptotic limit in anisotropic media Mohammad Asadzadeh
2001–04	A posteriori error estimation of functionals in elliptic problems: experiments Mats G. Larson and A. Jonas Niklasson
2001 - 05	A note on energy conservation for Hamiltonian systems using continuous time finite elements Peter Hansbo
2001 - 06	Stationary level set method for modelling sharp interfaces in groundwater flow Nahidh Sharif and Nils-Erik Wiberg
2001–07	Integration methods for the calculation of the magnetostatic field due to coils Marzia Fontana
2001–08	Adaptive finite element computation of 3D magnetostatic problems in potential formulation Marzia Fontana
2001–09	Multi-adaptive galerkin methods for ODEs I: theory & algorithms Anders Logg
2001–10	Multi-adaptive galerkin methods for ODEs II: applications Anders Logg
2001–11	Energy norm a posteriori error estimation for discontinuous Galerkin methods Roland Becker, Peter Hansbo, and Mats G. Larson
2001–12	Analysis of a family of discontinuous Galerkin methods for elliptic problems: the one dimensional case Mats G. Larson and A. Jonas Niklasson
2001–13	Analysis of a nonsymmetric discontinuous Galerkin method for elliptic prob- lems: stability and energy error estimates Mats G. Larson and A. Jonas Niklasson
2001 - 14	A hybrid method for the wave equation Larisa Beilina, Klas Samuelsson and Krister Åhlander
2001 - 15	A finite element method for domain decomposition with non-matching grids Roland Becker, Peter Hansbo and Rolf Stenberg
2001 - 16	Application of stable FEM-FDTD hybrid to scattering problems Thomas Rylander and Anders Bondeson
2001–17	Eddy current computations using adaptive grids and edge elements Y. Q. Liu, A. Bondeson, R. Bergström, C. Johnson, M. G. Larson, and K. Samuelsson
2001 - 18	Adaptive finite element methods for incompressible fluid flow Johan Hoffman and Claes Johnson
2001–19	Dynamic subgrid modeling for time dependent convection-diffusion-reaction equations with fractal solutions Johan Hoffman

2001 - 20	Topics in adaptive computational methods for differential equations
	Claes Johnson, Johan Hoffman and Anders Logg
2001 - 21	An unfitted finite element method for elliptic interface problems
	Anita Hansbo and Peter Hansbo
2001 - 22	A P^2 -continuous, P^1 -discontinuous finite element method for the Mindlin-
	Reissner plate model
	Peter Hansbo and Mats G. Larson
2002 - 01	Approximation of time derivatives for parabolic equations in Banach space:
	constant time steps
	Yubin Yan
2002 - 02	Approximation of time derivatives for parabolic equations in Banach space:
	variable time steps
	Yubin Yan
2002-03	Stability of explicit-implicit hybrid time-stepping schemes for Maxwell's equa-
	tions Themas Dylander and Anders Dondsson
2002 04	A computational study of transition to turbulance in shear flow
2002-04	A computational study of transition to turbulence in shear flow
2002-05	Adaptive hybrid EEM/EDM methods for inverse scattering problems
2002-05	Larisa Beilina
2002-06	DOLFIN - Dynamic Object oriented Library for FINite element computation
	Johan Hoffman and Anders Logg
2002-07	Explicit time-stepping for stiff ODEs
	Kenneth Eriksson, Claes Johnson and Anders Logg
2002-08	Adaptive finite element methods for turbulent flow
	Johan Hoffman
2002 - 09	Adaptive multiscale computational modeling of complex incompressible fluid
	flow
	Johan Hoffman and Claes Johnson
2002 - 10	Least-squares finite element methods with applications in electromagnetics
	Rickard Bergström
2002 - 11	Discontinuous/continuous least-squares finite element methods for elliptic prob-
	lems
2002 12	Rickard Bergstrom and Mats G. Larson
2002-12	Discontinuous least-squares finite element methods for the Div-Curl problem
2002 12	Rickard Bergstrom and Mats G. Larson
2002-13	Doject orientea implementation of a general finite element code
2002 14	On adaptive strategies and error control in fracture mechanics
2002-14	Per Heintz and Klas Samuelsson
2002-15	A unified stabilized method for Stokes' and Darcu's equations
2002 10	Frik Burman and Peter Hansbo
2002-16	A finite element method on composite arids based on Nitsche's method
	Anita Hansbo, Peter Hansbo and Mats G. Larson
2002 - 17	Edge stabilization for Galerkin approximations of convection-diffusion prob-
-	lems
	Erik Burman and Peter Hansbo

18

MULTI-ADAPTIVE TIME INTEGRATION

2002 - 18	Adaptive strategies and error control for computing material forces in fracture
	mechanics Der Heintz Fredrik Largeen Deter Hanghe and Kenneth Punggeen
2002 10	A variable diffusion method for mech emosthing
2002-19	A variable alguston method for mesh smoothing
2002 01	A hybrid method for electic evenue
2003-01	A hybrid method for elastic waves
2003-02	Application of the local nonohtuse tetrahedral refinement techniques near
2003-02	Fichera-like corners
	L Beilina S Korotov and M Křížek
2003-03	Nitsche's method for counting non-matching meshes in fluid-structure vibration
2000 00	problems
	Peter Hansbo and Joakim Hermansson
2003-04	Crouzeix-Raviart and Raviart-Thomas elements for acoustic fluid-structure
	interaction
	Joakim Hermansson
2003 - 05	Smoothing properties and approximation of time derivatives in multistep back-
	ward difference methods for linear parabolic equations
	Yubin Yan
2003 - 06	Postprocessing the finite element method for semilinear parabolic problems
	Yubin Yan
2003 - 07	The finite element method for a linear stochastic parabolic partial differential
	equation driven by additive noise
	Yubin Yan
2003 - 08	A finite element method for a nonlinear stochastic parabolic equation
	Yubin Yan
2003-09	A finite element method for the simulation of strong and weak discontinuities
	in elasticity
2002 10	Anita Hansbo and Peter Hansbo
2003-10	Denald Esten Michael Helst, and Mats C. Larson
2003-11	Adaptive finite element / difference method for inverse electic scattering waves
2003-11	L Beilina
2003-12	A Lagrange multiplier method for the finite element solution of elliptic domain
2000 12	decomposition problems using non-matching meshes
	Peter Hansbo, Carlo Lovadina, Ilaria Perugia, and Giancarlo Sangalli
2003 - 13	A reduced P^1 -discontinuous Galerkin method
	R. Becker, E. Burman, P. Hansbo, and M. G. Larson
2003 - 14	Nitsche's method combined with space-time finite elements for ALE fluid-
	structure interaction problems
	Peter Hansbo, Joakim Hermansson, and Thomas Svedberg
2003 - 15	Stabilized Crouzeix-Raviart element for the Darcy-Stokes problem
	Erik Burman and Peter Hansbo
2003 - 16	Edge stabilization for the generalized Stokes problem: a continuous interior
	penalty method
	Erik Burman and Peter Hansbo

2003 - 17	A conservative flux for the continuous Galerkin method based on discontinuous
	enrichment
	Mats G. Larson and A. Jonas Niklasson
2003 - 18	$CAD-to-CAE\ integration\ through\ automated\ model\ simplification\ and\ adaptive$
	modelling
	K.Y. Lee, M.A. Price, C.G. Armstrong, M.G. Larson, and K. Samuelsson
2003 - 19	Multi-adaptive time integration
	Anders Logg

These preprints can be obtained from www.phi.chalmers.se/preprints